AMENDMENT Page 2 TCM127

Serial Number: 10/733,780

Filing Date: December 11, 2003

Title: System and Method for Providing Event Hysteresis in Network Management Systems

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the subject

application.

Listing of Claims:

What is claimed is:

1. (Currently Amended) A method of managing an event toggling between first and

second event states in a network management system, said method comprising:

determining if said event maintains one of said first and second states for a predetermined

amount of time; and

reporting said event as having one of said first and second states only after said one of

said first and second states is maintained for said predetermined amount of time,

wherein said reporting said event as having said one of said first and second states

comprises reporting said event as achieving said one of said first and second states at the actual

time of occurrence of a time associated with a last state change of said event.

2. (Original) A method according to claim 1, wherein said event is an alarm.

3. (Original) A method according to claim 2, wherein said first state is an alarm set

state, and said second state is an alarm clear state.

4. (Cancelled)

5. (Original) A method according to claim 1, said method further comprising

reporting a number of times said event toggled between said first and second states.

6. (Cancelled)
 AMENDMENT
 Page 3

 Serial Number: 10/733,780
 TCM127

Filing Date: December 11, 2003

Title: System and Method for Providing Event Hysteresis in Network Management Systems

7. (Original) A method according to claim 1, said method further comprising

reporting said event as being in a toggling condition.

8. (Original) A method according to claim 1, said method further comprising

reporting said event as not being in a toggling condition.

9. (Currently Amended) A method of managing an event toggling between first and

second event states in a network management system, said method comprising:

reporting said event as having said first state;

monitoring said event to determine if said event maintains said second state for a

predetermined amount of time; and

reporting said event as having said second state only after said second state is maintained

for said predetermined amount of time,

wherein said reporting said event as having said second state comprises reporting said

event has achieving said second state at the actual time of occurrence of a time associated with a

last state change of said event.

10. (Original) A method according to claim 9, wherein said event is an alarm.

11. (Original) A method according to claim 10, wherein said first state is an alarm set

state, and said second state is an alarm clear state.

12. (Cancelled).

AMENDMENT Page 4 TCM127 Serial Number: 10/733,780

Filing Date: December 11, 2003

Title: System and Method for Providing Event Hysteresis in Network Management Systems

13. (Original) A method according to claim 9, said method further comprising

reporting said number of times said event toggled between said first and second states.

14. (Cancelled).

15. (Original) A method according to claim 9, said method further comprising

reporting said event as being in a toggling condition.

16. (Original) A method according to claim 9, said method further comprising

reporting said event as not being in a toggling condition.

17. (Currently Amended) A machine-readable medium whose contents cause a

network management system to perform a method of managing an event toggling between first

and second event states, said method comprising:

determining if said event maintains one of said first and second states for a predetermined

amount of time; and

reporting said event as having one of said first and second states only after said one of

said first and second states is maintained for said predetermined amount of time,

wherein said reporting said event as having said one of said first and second states

comprises reporting said event as achieving said one of said first and second states at the actual

time of occurrence of a time associated with a last state change of said event.

18. (Original) The machine readable medium of claim 17, wherein said event is an

alarm.

AMENDMENT Page 5 TCM127 Serial Number: 10/733,780

Filing Date: December 11, 2003

Title: System and Method for Providing Event Hysteresis in Network Management Systems

19. (Original) The machine readable medium of claim 18, wherein said first state is an

alarm set state, and said second state is an alarm clear state.

20. (Cancelled).

21. (Original) The machine readable medium of claim 17, said method further

comprising reporting a number of times said event toggles between said first and second states.

22. (Cancelled).

23. (Original) The machine readable medium of claim 17, said method further

comprising reporting said event as being in a toggling condition.

24. (Original) The machine readable medium of claim 17, said method further

comprising reporting said event as not being in a toggling condition.

25. (Currently Amended) A network management system comprising:

a machine-readable medium whose contents cause said system to perform a method of

managing an event toggling between first and second event states, the method comprising:

determining if said event maintains one of said first and second states for a predetermined

amount of time; and

reporting said event as having one of said first and second states only after said one of

said first and second states is maintained for said predetermined amount of time,

wherein said reporting said event as having said one of said first and second states

comprises reporting said event as achieving said one of said first and second states at the actual

time of occurrence of a time associated with a last state change of said event.

26. (Original) The system of claim 25, wherein said event is an alarm.

AMENDMENT Page 6 Serial Number: 10/733,780 TCM127

Filing Date: December 11, 2003

Title: System and Method for Providing Event Hysteresis in Network Management Systems

27. (Original) The system of claim 26, wherein said first state is an alarm set state,

and said second state is an alarm clear state.

28. (Cancelled).

29. (Original) The system of claim 25, said method further comprising reporting said

number of times said event toggled between said first and second states.

30. (Cancelled).

31. (Original) The system of claim 25, said method further comprising reporting said

event as being in a toggling condition.

32. (Original) The system of claim 25, said method further comprising reporting said

event as not being in a toggling condition.

33. (Currently Amended) An optical communication system comprising:

at least one transmitter for transmitting an optical signal to a receiver through an optical

information channel, at least one of said transmitter, said receiver and said optical information

channel comprising at least one apparatus for reporting an event; and

a network management system coupled to the optical communication system for

receiving said report of said event, said network management system comprising a machine-

readable medium whose contents cause said network management system to perform a method

comprising:

determining if said event maintains one of a first and a second state for a predetermined

amount of time; and

reporting said event as having one of said first and second states only after said one of

said first and second states is maintained for said predetermined amount of time,

AMENDMENT TCM127

Serial Number: 10/733,780

Filing Date: December 11, 2003

Title: System and Method for Providing Event Hysteresis in Network Management Systems

wherein said reporting said event as having said one of said first and second states

Page 7

comprises reporting said event as achieving said one of said first and second states at the actual

time of occurrence of a time associated with a last state change of said event.

34. (Original) The system of claim 33, wherein said event is an alarm.

35. (Original) The system of claim 34, wherein said first state is an alarm set state,

and said second state is an alarm clear state.

(Cancelled). 36.

37. (Original) The system of claim 33, said method further comprising reporting a

number of times said event toggled between said first and second states.

38. (Cancelled).

39. (Original) The system of claim 33, said method further comprising reporting said

event as being in a toggling condition.

40. (Original) The system of claim 33, said method further comprising reporting said

event as not being in a toggling condition.